

EUROPEAN SAFETY DATA SHEET

SAFETY DATA SHEET

Page 1 of 3

HumiSeal Thinner 600

Revision 3
Revision date 13-Jul-2006

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name HumiSeal Thinner 600

Company HumiSeal Europe
Alasan House
Albany Park
Frimley Road
Camberley
Surrey
GU16 7PH
United Kingdom

Telephone +44 (0)127 6691100

Fax +44 (0)127 6691227

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
2-methoxy-1-methylethyl acetate (1-Methoxypropylacetate)	80-90%	108-65-6	203-603-9	R10 Xi; R36
2-Methoxypropyl acetate	0-0.5%	70657-70-4	274-724-2	R10 Repr Cat 2; R61 Xi; R37

3. HAZARDS IDENTIFICATION

Main hazards Flammable Irritating to eyes.

4. FIRST AID MEASURES

Skin contact Wash off immediately with plenty of soap and water.

Eye contact Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention.

Inhalation Move the exposed person to fresh air.

Ingestion DO NOT INDUCE VOMITING. Seek medical attention.

General information Immediate medical attention is required.

5. FIRE FIGHTING MEASURES

Extinguishing media Use as appropriate: carbon dioxide (CO₂), dry chemical, foam.

Protective equipment Wear suitable respiratory equipment when necessary.

**Manufactured by: Humiseal Europe,
Alasan House, Albany Park, Frimley Road, Camberley, Surrey, GU16 7PH, England
Phone: 44-127-669-1100 Fax: 44-127-669-1227**

Print date 19-Dec-2006

HumiSeal Thinner 600

Revision 3
Revision date 13-Jul-2006

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	Ensure adequate ventilation of the working area.
Environmental precautions	Do not allow product to enter drains.
Clean up methods	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal.

7. HANDLING AND STORAGE

Handling	Ensure adequate ventilation of the working area.
Storage	Store in original container. Store at temperatures between 5 °C and 25 °C. Keep in a cool, dry, well ventilated area. Keep containers tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits

2-methoxy-1-methylethyl acetate (1-Methoxypropylacetate)	WEL 8-hr limit ppm: 50 WEL 15 min limit ppm: 100	WEL 8-hr limit mg/m3: 274 WEL 15 min limit mg/m3: 548
---	---	--

Respiratory protection	Wear suitable respiratory equipment when necessary. Wear: Suitable respiratory equipment.
Hand protection	Chemical resistant gloves (PVC)
Eye protection	Avoid contact with eyes. In case of splashing, wear: Safety glasses.
Protective equipment	Avoid contact with eyes and skin.

9. PHYSICAL AND CHEMICAL PROPERTIES

Description	Liquid.
Colour	Colourless.
Odour	Strong.
Flash point	45°C

10. STABILITY AND REACTIVITY

Stability	Stable.
Materials to avoid	Strong oxidising agents.
Hazardous decomposition products	Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Corrosivity	Irritating to eyes, respiratory system and skin.
Repeated or prolonged exposure	Repeated or prolonged exposure may cause dermatitis.

12. ECOLOGICAL INFORMATION

13. DISPOSAL CONSIDERATIONS

General information	Dispose of as special waste in compliance with local and national regulations.
----------------------------	--

Manufactured by: Humiseal Europe,
Alasan House, Albany Park, Frimley Road, Camberley, Surrey, GU16 7PH, England
Phone: 44-127-669-1100 Fax: 44-127-669-1227

Print date 19-Dec-2006

HumiSeal Thinner 600

Revision 3
Revision date 13-Jul-2006

14. TRANSPORT INFORMATION

ADR/RID

UN 1263	Packing group II
Class 3	Hazard ID 33
Proper Shipping Name PAINT RELATED MATERIAL	

IMDG

UN 1263	Packing group II
Class 3	Marine pollutant .
EmS Code F-E S-E	

IATA

UN 1263	Packing group II
Class 3	Subsidiary risk -
Packing Instruction 307 (Cargo)	Maximum quantity 60 L
Packing Instruction 305 (Passenger)	Maximum quantity 5 L

15. REGULATORY INFORMATION

Symbols Xi - Irritant



Risk phrases R10 - Flammable.
R36 - Irritating to eyes.

Safety phrases S2 - Keep out of the reach of children.
S25 - Avoid contact with eyes.

16. OTHER INFORMATION

Text of risk phrases in Section 2 R10 - Flammable.
R36 - Irritating to eyes.
R37 - Irritating to respiratory system.
R61 - May cause harm to the unborn child.

Further information The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. The information provided relates only to the product or material specified and does not apply if used in combination with other materials. Handle and store under inert gas. This product is not properly labelled for sale or use outside the EU.

Manufactured by: Humiseal Europe,
Alasan House, Albany Park, Frimley Road, Camberley, Surrey, GU16 7PH, England
Phone: 44-127-669-1100 Fax: 44-127-669-1227

Print date 19-Dec-2006